

Printing date 08.02.2019 Revision: 08.02.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: MANNOL 9671 Motor Kaltreiniger 450ml
- 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Cleaning agent/ Cleaner
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SCT-Vertriebs GmbH Feldstrasse 154 22880 WEDEL DEUTSCHLAND info@sct-germany.de

- · Further information obtainable from: Product safety department.
- 1.4 Emergency telephone number: Giftinformationszentrum-Nord +49-551-19240

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 2 H223-H229 Flammable aerosol. Pressurised container: May burst if heated.



GHS08 health hazard

Repr. 2 H361d Suspected of damaging the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02 GHS07 GHS08

(Contd. on page 2)



Printing date 08.02.2019 Revision: 08.02.2019

Trade name: MANNOL 9671 Motor Kaltreiniger 450ml

(Contd. of page 1)

· Signal word Danger

· Hazard-determining components of labelling:

toluene

· Hazard statements

H223-H229 Flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

Suspected of damaging the unborn child. H361d

H336 May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure. H373

H304 May be fatal if swallowed and enters airways.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P301+P310

Specific treatment (see on this label). P321

Do NOT induce vomiting. P331

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

Take off contaminated clothing and wash it before reuse. P362+P364

Store locked up. P405

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable. · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:			
CAS: 108-88-3	toluene	10-<22%	
EINECS: 203-625-9	Flam. Liq. 2, H225; Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304; Skin Irrit. 2, H315; STOT SE 3, H336		
CAS: 106-97-8	butane	5–<15%	
EINECS: 203-448-7	Flam. Gas 1, H220; Press. Gas C, H280		
CAS: 111-76-2	2-butoxyethanol	5-<10%	
EINECS: 203-905-0	Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319		
CAS: 74-98-6	propane	1–<5%	
EINECS: 200-827-9	Flam. Gas 1, H220; Press. Gas C, H280		
CAS: 14409-72-4	26-(4-nonylphenoxy)-3,6,9,12,15,18,21,24-Octaoxahexacosan-1-	1.5-<2.5%	
EC number: 604-395-6			
	Aquatic Chronic 2, H411; Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319		

(Contd. on page 3)



Printing date 08.02.2019 Revision: 08.02.2019

Trade name: MANNOL 9671 Motor Kaltreiniger 450ml

		(Contd. of page 2
CAS: 42615-29-2	Benzene Sulphonic acid, alkyl derivs.	1.5-<2.5%
EC number: 610-046-	9 Skin Corr. 1C, H314; Acute Tox. 4, H302	
CAS: 532-32-1	sodium benzoate	0.5-<2%
EINECS: 208-534-8	Eye Irrit. 2, H319	
· Not dangerous subs	tances	
CAS: 102-71-6	- Friethanolamine	1–<5%
EINECS: 203-049-8		
CAS: 68603-42-9	coconut oil diethanolamine condensate	1-<5%
CAS: 9005-65-6	CAS: 9005-65-6 Sorbitan monooleate, ethoxylated	
NLP: 500-019-9	•	
CAS: 7732-18-5	vater, distilled, conductivity or of similar purity	20-<35%
EINECS: 231-791-2		
SVHC		,
14409-72-4 26-(4-nor	nylphenoxy)-3,6,9,12,15,18,21,24-Octaoxahexacosan-1-ol	

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Take affected persons out into the fresh air.

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.

Additional information: For the wording of the listed hazard phrases refer to section 16.

· After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2. Do not use water.

Use fire extinguishing methods suitable to surrounding conditions.

Foam

Fire-extinguishing powder

Sand

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- 5.3 Advice for firefighters
- · **Protective equipment:** Mouth respiratory protective device.

(Contd. on page 4)



Printing date 08.02.2019 Revision: 08.02.2019

Trade name: MANNOL 9671 Motor Kaltreiniger 450ml

(Contd. of page 3)

· Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Particular danger of slipping on leaked/spilled product.

Wear protective clothing.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

108-88-3 toluene (22.0%)

WEL Short-term value: 384 mg/m³, 100 ppm Long-term value: 191 mg/m³, 50 ppm

Sk

(Contd. on page 5)



Printing date 08.02.2019 Revision: 08.02.2019

Trade name: MANNOL 9671 Motor Kaltreiniger 450ml

(Contd. of page 4)

106-97-8 butane (15.0%)

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

111-76-2 2-butoxyethanol (10.0%)

WEL Short-term value: 246 mg/m³, 50 ppm Long-term value: 123 mg/m³, 25 ppm Sk, BMGV

· Ingredients with biological limit values:

111-76-2 2-butoxyethanol (10.0%)

BMGV 240 mmol/mol creatinine

Medium: urine

Sampling time: post shift Parameter: butoxyacetic acid

· Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)



Printing date 08.02.2019 Revision: 08.02.2019

Trade name: MANNOL 9671 Motor Kaltreiniger 450ml

· Eye protection:

(Contd. of page 5)



Tightly sealed goggles

· Body protection: Light weight protective clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Liquid Colour: White

Odour: CharacteristicOdour threshold: Not determined.

• **pH-value at 20 °C:** 9.63

Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: Not applicable, as aerosol.

· Flash point: Not applicable, as aerosol.

· Flammability (solid, gas): Not applicable.

• **Decomposition temperature:** Not determined.

· **Auto-ignition temperature:** Product is not selfigniting.

• Explosive properties: Not determined.

· Explosion limits:

Lower: 1.1 Vol % **Upper:** 10.6 Vol %

· Vapour pressure: Not determined.

Density at 20 °C: 0.95 g/cm³
 Relative density Not determined.
 Vapour density Not determined.
 Evaporation rate Not applicable.

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

· Solvent content:

 Organic solvents:
 22-<57 %</td>

 Water:
 20-<35 %</td>

(Contd. on page 7)



Printing date 08.02.2019 Revision: 08.02.2019

Trade name: MANNOL 9671 Motor Kaltreiniger 450ml

(Contd. of page 6)

VOC (EC) 22–<57 %

9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:

Carbon monoxide

Aldehyde

Poisonous gases/vapours

Carbon dioxide

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	· LD/LC50 values relevant for classification:			
ATE (Acu	ATE (Acute Toxicity Estimates)			
Oral	LD50	>5,968–10,663 mg/kg		
Dermal	LD50	>4,000–8,000 mg/kg (rab)		
Inhalative	LC50/4 h	>110–220 mg/l		
108-88-3 1	108-88-3 toluene			
Oral	LD50	5,000 mg/kg (rat)		
Dermal	LD50	12,124 mg/kg (rabbit)		
Inhalative	LC50/4 h	5,320 mg/l (mouse)		
106-97-8 I	106-97-8 butane			
Inhalative	LC50/4 h	658 mg/l (rat)		
111-76-2	111-76-2 2-butoxyethanol			
Oral	LD50	1,480 mg/kg (rat)		
Dermal	LD50	400 mg/kg (rab)		
532-32-1	532-32-1 sodium benzoate			
Oral	LD50	4,070 mg/kg (rat)		
. Drimon, i	· Primary irritant offoct:			

- · Primary irritant effect:
- Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

· Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

(Contd. on page 8)



Printing date 08.02.2019 Revision: 08.02.2019

Trade name: MANNOL 9671 Motor Kaltreiniger 450ml

(Contd. of page 7)

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity

Suspected of damaging the unborn child.

STOT-single exposure

May cause drowsiness or dizziness.

· STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

· Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue		
HP 3	Flammable	
HP 4	Irritant - skin irritation and eye damage	
HP 5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity	
HP 10	Toxic for reproduction	

- Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

- · 14.1 UN-Number
- · ADR, IMDG, IATA

UN1950

(Contd. on page 9)



Printing date 08.02.2019 Revision: 08.02.2019

Trade name: MANNOL 9671 Motor Kaltreiniger 450ml

(Contd. of page 8) · 14.2 UN proper shipping name · ADR 1950 AEROSOLS · IMDG **AEROSOLS** · IATA AEROSOLS, flammable · 14.3 Transport hazard class(es) · ADR 2 5F Gases. · Class · Label 2.1 · IMDG, IATA · Class 2.1 · Label 2.1 · 14.4 Packing group · ADR, IMDG, IATA not regulated · 14.5 Environmental hazards: Not applicable. · 14.6 Special precautions for user Warning: Gases. Danger code (Kemler): · EMS Number: F-D.S-U · Stowage Code SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of · Segregation Code 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. · Transport/Additional information: · Limited quantities (LQ) 1L · Excepted quantities (EQ) Code: E0 Not permitted as Excepted Quantity · Transport category



Printing date 08.02.2019 Revision: 08.02.2019

Trade name: MANNOL 9671 Motor Kaltreiniger 450ml

	(Contd. of page 9)
· Tunnel restriction code	D
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

· LIST OF SUBSTANCES SUBJECT TO AUTHORISATION (ANNEX XIV)				
14409-72-4 26-(4-nonylphenoxy)-3,6,9,12,15,18,21,24-Octaoxahexacosan-	Sunset date: 2021-01-04			

- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 48
- · National regulations:
- · Other regulations, limitations and prohibitive regulations
- Substances of very high concern (SVHC) according to REACH, Article 57 14409-72-4 26-(4-nonylphenoxy)-3,6,9,12,15,18,21,24-Octaoxahexacosan-1-ol
 - · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.
- H361d Suspected of damaging the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 11)



Printing date 08.02.2019 Revision: 08.02.2019

Trade name: MANNOL 9671 Motor Kaltreiniger 450ml

(Contd. of page 10)

· **Department issuing SDS:** Product safety department.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Flam. Gas 1: Flammable gases – Category 1

Aerosol 2: Aerosols - Category 2

Press. Gas C: Gases under pressure - Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1C: Skin corrosion/irritation - Category 1C

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Repr. 2: Reproductive toxicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

* Data compared to the previous version altered.

GB -