

Printing date 08.04.2019 Revision: 08.04.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: MANNOL 9901 2K-Acryl Fix Bond 30g/24ml (Glue A white)
- 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Adhesives
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SCT-Vertriebs GmbH Feldstrasse 154 22880 WEDEL DEUTSCHLAND info@sct-germany.de

- · Further information obtainable from: Product safety department.
- 1.4 Emergency telephone number: Giftinformationszentrum-Nord +49-551-19240

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS05 corrosion

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Acute Tox. 4 H312 Harmful in contact with skin.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H335 May cause respiratory irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms





GHS05 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

methacrylic acid methyl methacrylate

Buta-1,3-diene; ethenylbenzene; prop-2-enenitrile



Printing date 08.04.2019 Revision: 08.04.2019

Trade name: MANNOL 9901 2K-Acryl Fix Bond 30g/24ml (Glue A white)

(Contd. of page 1)

triethylamine

Hazard statements

H302+H312 Harmful if swallowed or in contact with skin. H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction. H335 May cause respiratory irritation.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous componen	ts:	
CAS: 80-62-6 EINECS: 201-297-1	methyl methacrylate	41–45%
EINECS: 201-297-1	Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	
CAS: 9003-56-9	Buta-1,3-diene; ethenylbenzene; prop-2-enenitrile	20–26.5%
EC number: 618-371-8	Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	
CAS: 79-41-4	methacrylic acid	20–24%
EINECS: 201-204-4	Skin Corr. 1A, H314; Acute Tox. 4, H302; Acute Tox. 4, H312	
CAS: 2782-91-4	tetramethyl-2-thiourea	1–2.94%
EINECS: 220-488-0	Acute Tox. 4, H302	
CAS: 121-44-8	triethylamine	1–1.5%
EINECS: 204-469-4	Flam. Liq. 2, H225; Skin Corr. 1A, H314; Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	
CAS: 123-31-9	1,4-dihydroxybenzene	0.01-0.06%
EINECS: 204-617-8	Muta. 2, H341; Carc. 2, H351; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=10); Acute Tox. 4, H302; Skin Sens. 1, H317	

· Additional information: For the wording of the listed hazard phrases refer to section 16.



Printing date 08.04.2019 Revision: 08.04.2019

Trade name: MANNOL 9901 2K-Acryl Fix Bond 30g/24ml (Glue A white)

(Contd. of page 2)

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing:

Call for a doctor immediately.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2. Do not use water.

Use fire extinguishing methods suitable to surrounding conditions.

Foam

Fire-extinguishing powder

Sand

- · For safety reasons unsuitable extinguishing agents: Water
- · 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.
- Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Particular danger of slipping on leaked/spilled product.

Wear protective clothing.

- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent.

Dispose contaminated material as waste according to item 13.

(Contd. on page 4)



Printing date 08.04.2019 Revision: 08.04.2019

Trade name: MANNOL 9901 2K-Acryl Fix Bond 30g/24ml (Glue A white)

(Contd. of page 3)

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about fire and explosion protection: Keep respiratory protective device available.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:	
80-62-6 methyl methacrylate (46.0%)	

			•	,
WEL	Short-term	value: 416	mg/m³	, 100 ppn
	Long-term	value: 208	mg/m³	, 50 ppm

79-41-4 methacrylic acid (24.0%)

WEL	Short-term value: 143 mg/m³, 40 ppm
	Long-term value: 72 mg/m³, 20 ppm

121-44-8 triethylamine (2.0%)

WEL Short-term value: 17 mg/m³, 4 ppm Long-term value: 8 mg/m³, 2 ppm Sk

123-31-9 1,4-dihydroxybenzene (0.06%)

WEL Long-term value: 0.5 mg/m³

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

(Contd. on page 5)



Printing date 08.04.2019 Revision: 08.04.2019

Trade name: MANNOL 9901 2K-Acryl Fix Bond 30g/24ml (Glue A white)

(Contd. of page 4)

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Pasty
Colour: White
Odour: Characteristic

· Odour threshold: Characteristic Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: 101 $^{\circ}\text{C}$

Flash point: Not applicable.

· Flammability (solid, gas): Not applicable.

· Ignition temperature: 430 °C

· **Decomposition temperature:** Not determined.

• Auto-ignition temperature: Product is not selfigniting.

(Contd. on page 6)



Printing date 08.04.2019 Revision: 08.04.2019

Trade name: MANNOL 9901 2K-Acryl Fix Bond 30g/24ml (Glue A white)

	(Contd. of page 5)
· Explosive properties:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	2.1 Vol %
Upper:	12.5 Vol %
· Vapour pressure at 20 °C:	47 hPa
· Density:	Not determined.
Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
VOC (EC)	0.00 %
Solids content:	23–30.1 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:

Carbon monoxide

Aldehyde

Poisonous gases/vapours

Carbon dioxide

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

Harmful if swallowed or in contact with skin.

ΔTE	(Acuto	Toxicity	Estimates'	·
$\Delta I = 1$	IACULE	IUXICILV	LSIIIIIaies	,

Oral	LD50	1,248–1	,690	mg/	kg

(Contd. on page 7)



Printing date 08.04.2019 Revision: 08.04.2019

Trade name: MANNOL 9901 2K-Acryl Fix Bond 30g/24ml (Glue A white)

		(Contd. of page 6)
Dermal	LD50	1,975–2,395 mg/kg (rabbit)
Inhalative	LC50/4 h	733–1,100 mg/l
80-62-6 m	ethyl met	hacrylate
Oral	LD50	7,872 mg/kg (rat)
79-41-4 m	ethacrylic	acid
Oral	LD50	1,332 mg/kg (mouse)
Dermal	LD50	500 mg/kg (rabbit)
121-44-8 t	riethylam	ine
Oral	LD50	460 mg/kg (rat)
Dermal	LD50	570 mg/kg (rabbit)
123-31-9 ′	1,4-dihydr	oxybenzene
Oral	LD50	320 mg/kg (rat)
Duimaamain		-1-

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes severe skin burns and eye damage.

· Serious eye damage/irritation

Causes serious eye damage.

- · Respiratory or skin sensitisation
- May cause an allergic skin reaction.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause respiratory irritation.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into the ground.

- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.
- 12.6 Other adverse effects No further relevant information available.



Printing date 08.04.2019 Revision: 08.04.2019

Trade name: MANNOL 9901 2K-Acryl Fix Bond 30g/24ml (Glue A white)

(Contd. of page 7)

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Europ	· European waste catalogue	
HP 5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity	
HP 6	Acute Toxicity	
HP 8	Corrosive	
HP 13	Sensitising	

- · Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.

· 14.1 UN-Number · ADR, IMDG, IATA UN1760	
• 14.2 UN proper shipping name • ADR 1760 CORROSIVE	LIQUID, N.O.S
(METHACRYLIC AC TRIETHYLAMINE) • IMDG, IATA CORROSIVE LIQUID, N ACID, STABILIZED, TRIET	.O.S. (METHACRYLIC
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
· Class 8 Corrosive substances.	
· Label 8	
· 14.4 Packing group · ADR, IMDG, IATA	
• 14.5 Environmental hazards: Not applicable.	
• 14.6 Special precautions for user Warning: Corrosive substar	nces.
Danger code (Kemler): 80	
EMS Number: F-A,S-B	
· Segregation groups Acids	
· Stowage Category B	
 Stowage Code SW2 Clear of living quarters 	3.
otomage dodd	
· 14.7 Transport in bulk according to Annex II of	
<u> </u>	



Printing date 08.04.2019 Revision: 08.04.2019

Trade name: MANNOL 9901 2K-Acryl Fix Bond 30g/24ml (Glue A white)

	(Contd. of page
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
Transport category	2
Tunnel restriction code	E
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2
,	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1760 CORROSIVE LIQUID, N.O.S
-	(METHACRYLIC ACID, STABILIZED
	TRIETHYLAMINE), 8, II

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H341 Suspected of causing genetic defects.

H351 Suspected of causing cancer.

H400 Very toxic to aquatic life.

· Department issuing SDS: Product safety department.

Contact: Mrs. Zubaite

(Contd. on page 10)



Printing date 08.04.2019 Revision: 08.04.2019

Trade name: MANNOL 9901 2K-Acryl Fix Bond 30g/24ml (Glue A white)

(Contd. of page 9)

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Acute Tox. 4: Acute toxicity – Category 4 Skin Corr. 1A: Skin corresion/irritation – Category

Skin Corr. 1A: Skin corrosion/irritation – Category 1A Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1 Muta. 2: Germ cell mutagenicity – Category 2

Carc. 2: Carcinogenicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

* Data compared to the previous version altered.

GB