Printing date 09.10.2019

Safety data sheet according to 1907/2006/EC, Article 31

Version number 1910

Revision: 09.10.2019

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

- Trade name: MANNOL 9953 Silicone Spray 200ml
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- · Application of the substance / the mixture Lubricant
- 1.3 Details of the supplier of the safety data sheet

• Manufacturer/Supplier: SCT-Vertriebs GmbH Feldstrasse 154 22880 WEDEL DEUTSCHLAND info@sct-germany.de

• Further information obtainable from: Product safety department.

• 1.4 Emergency telephone number: Giftinformationszentrum-Nord +49-551-19240

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 GHS02 flame Flam. Liq. 2 H225 Highly flammable liquid and vapour. GHS08 health hazard H304 May be fatal if swallowed and enters airways. Asp. Tox. 1 GHS09 environment Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects. GHS07 Skin Irrit. 2 H315 Causes skin irritation. STOT SE 3 H336 May cause drowsiness or dizziness. · 2.2 Label elements Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. (Contd. on page 2) GB

Revision: 09.10.2019

Printing date 09.10.2019

Version number 1910

Trade name: MANNOL 9953 Silicone Spray 200ml

(Contd. of page 1) · Hazard pictograms GHS02 GHS07 GHS08 GHS09 · Signal word Danger · Hazard-determining components of labelling: hexane (containing < 5 % n-hexane (203-777-6)) Orange oil · Hazard statements H225 Highly flammable liquid and vapour. H315 Causes skin irritation. H336 May cause drowsiness or dizziness. H304 May be fatal if swallowed and enters airways. H411 Toxic to aquatic life with long lasting effects. · Precautionary statements P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P103 Read label before use. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. P240 P241 Use explosion-proof electrical/ventilating/lighting equipment. Avoid breathing dust/fume/gas/mist/vapours/spray. P261 Use only outdoors or in a well-ventilated area. P271 P280 Wear protective gloves/protective clothing/eye protection/face protection. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. Specific treatment (see on this label). P321 P331 Do NOT induce vomiting. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Take off contaminated clothing and wash it before reuse. P362+P364 Collect spillage. P391 P405 Store locked up. P501 Dispose of contents/container in accordance with local/regional/national/international regulations. Additional information: EUH208 Contains Orange oil, (R)-p-mentha-1,8-diene. May produce an allergic reaction. · 2.3 Other hazards · Results of PBT and vPvB assessment · **PBT:** Not applicable.

• **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

GB -

GERMANY

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.10.2019

Version number 1910

Revision: 09.10.2019

Trade name: MANNOL 9953 Silicone Spray 200ml

		(Contd. of page 2)		
Dangerous compone	nts:			
CAS: 106-97-8	butane	20-40.5%		
EINECS: 203-448-7	Flam. Gas 1, H220; Press. Gas C, H280			
CAS: 107-83-5	hexane (containing < 5 % n-hexane (203-777-6))	10–25%		
EINECS: 203-523-4	Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336			
CAS: 74-98-6	propane	10–19%		
EINECS: 200-827-9	Flam. Gas 1, H220; Press. Gas C, H280			
CAS: 8008-57-9	Orange oil	0.035-0.25%		
EC number: 307-891-8	³ Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317			
CAS: 5989-27-5 EINECS: 227-813-5	(R)-p-mentha-1,8-diene	0.015-0.125%		
	Flam. Liq. 3, H226; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; Skin Sens. 1, H317			
Not dangerous substances				
CAS: 9006-65-9 D	limethicone	5–15%		
CAS: 110-98-5 D	0-98-5 Dipropylene glycol			
EINECS: 203-821-4				
Additional informatio	n: For the wording of the listed hazard phrases refer to section 1	6.		

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

[·] 5.1 Extinguishing media

· Suitable extinguishing agents:

CO2. Do not use water.

Use fire extinguishing methods suitable to surrounding conditions.

Foam

Fire-extinguishing powder

Sand

- · For safety reasons unsuitable extinguishing agents: Water
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- Protective equipment: No special measures required.

(Contd. on page 4)

GB

Printing date 09.10.2019

Safety data sheet according to 1907/2006/EC, Article 31

Version number 1910

Revision: 09.10.2019

Trade name: MANNOL 9953 Silicone Spray 200ml

· Additional information

(Contd. of page 3)

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation Particular danger of slipping on leaked/spilled product. Wear protective clothing.
 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

• **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

- · Information about fire and explosion protection: No special measures required.
- 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

106-97-8 butane (40.5%)

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm

Carc (if more than 0.1% of buta-1.3-diene)

• Additional information: The lists valid during the making were used as basis.

(Contd. on page 5)

GB

Version number 1910

Revision: 09.10.2019

Trade name: MANNOL 9953 Silicone Spray 200ml

(Contd. of page 4)

- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the skin. Avoid contact with the eves and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

• Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling

SECTION 9: Physical and chemical properties

General Information		
Appearance:		
Form:	Liquid	
Colour:	Yellow	
Odour:	Characteristic	
Odour threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/freezing point:	Undetermined.	
Initial boiling point and boiling	range: Undetermined.	
Flash point:	-97 °C	
Flammability (solid, gas):	Not applicable.	



Printing date 09.10.2019



Printing date 09.10.2019

Version number 1910

Revision: 09.10.2019

Trade name: MANNOL 9953 Silicone Spray 200ml

	(Contd. of page 5)
· Ignition temperature:	230–315 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product does not present an explosion hazard.
 Explosion limits: Lower: Upper: 	Not determined. Not determined.
· Vapour pressure:	Not determined.
 Density at 20 °C: Relative density Vapour density Evaporation rate 	0.75 g/cm ³ Not determined. Not determined. Not determined.
 Solubility in / Miscibility with water: 	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
 Viscosity: Dynamic: Kinematic: 	Not determined. Not determined.
 Solvent content: Organic solvents: VOC (EC) 	30–59.8 % 40–84.5 %
Solids content: 9.2 Other information	0.0 % No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- 10.6 Hazardous decomposition products:
- Carbon monoxide
- Aldehyde
- Poisonous gases/vapours
- Carbon dioxide

(Contd. on page 7)

Printing date 09.10.2019

Version number 1910

Revision: 09.10.2019

Trade name: MANNOL 9953 Silicone Spray 200ml

(Contd. of page 6)

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

106-97-8 butane

Inhalative LC50/4 h 658 mg/l (rat)

· Primary irritant effect:

• Skin corrosion/irritation Causes skin irritation.

- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure
- May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

- 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies.

- Toxic for aquatic organisms
- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 8)

accor

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.10.2019

Version number 1910

Revision: 09.10.2019

(Contd. of page 7)

Trade name: MANNOL 9953 Silicone Spray 200ml

· European waste catalogue

HP4 Irritant - skin irritation and eye damage

HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

HP14 Ecotoxic

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number	
ADR, IMDG, IATA	UN1139
14.2 UN proper shipping name	
ADR	1139 COATING SOLUTION, ENVIRONMENTALLY HAZARDOUS
IMDG	COATING SOLUTION (hexane (containing < 5 % n
	hexane (203-777-6)), Orange oil), MARINE
ΙΑΤΑ	POLLUTANT COATING SOLUTION
14.3 Transport hazard class(es)	
ADR, IMDG	
Class	3 Flammable liquids.
Label	3
Class	3 Flammable liquids.
Label	3
14.4 Packing group	
ADR, IMDG, IATA	
14.5 Environmental hazards:	Product contains environmentally hazardous substances: hexane (containing < 5 % n-hexane (203-777-6))
Marine pollutant:	Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	33



Printing date 09.10.2019

Version number 1910

Revision: 09.10.2019

Trade name: MANNOL 9953 Silicone Spray 200ml

	(Contd. of page 8)
· Stowage Category	В
 14.7 Transport in bulk according to Ann Marpol and the IBC Code 	nex II of Not applicable.
· Transport/Additional information:	
 ADR Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
 Transport category Tunnel restriction code 	2 D/E
 IMDG Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1139 COATING SOLUTION, 3, 11, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

¹ 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category E2 Hazardous to the Aquatic Environment
- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H336 May cause drowsiness or dizziness.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

(Contd. on page 10)

⁻ GB



Printing date 09.10.2019

Version number 1910

Revision: 09.10.2019

Trade name: MANNOL 9953 Silicone Spray 200ml

(Contd. of page	9)
H411 Toxic to aquatic life with long lasting effects.	'
 Department issuing SDS: Product safety department. 	
· Abbreviations and acronyms:	
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning ti	he
International Carriage of Dangerous Goods by Road)	
IMDG: International Maritime Code for Dangerous Goods	
IATA: International Air Transport Association	
GHS: Globally Harmonised System of Classification and Labelling of Chemicals	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
VOC: Volatile Organic Compounds (USA, EU)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
Flam. Gas 1: Flammable gases – Category 1 Press. Gas C: Gases under pressure – Compressed gas	
Flam. Lig. 2: Flammable liguids – Category 2	
Flam. Liq. 3: Flammable liquids – Category 3	
Skin Irrit. 2: Skin corrosion/irritation – Category 2	
Skin Sens. 1: Skin sensitisation – Category 1	
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
Asp. Tox. 1: Aspiration hazard – Category 1	
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1	
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1	
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2	
* Data compared to the previous version altered.	