

Product Code:

# 2501

# MULTIFARM STOU

Agricultural machinery oil

Meets the requirements:

SAE 10W-30 ACEA E3 API CG-4/SF, GL-4  
NEW HOLLAND ESN-M2C 134D/ESN-M2C 159B/  
ESN-M2C 134C/ MAT 3525/ MAT 3526  
JOHN DEERE J27/J20C/J20D  
MASSEY FERGUSON CMS M 113/ CMS M 1139/  
CMS M 1144/ CMS M 1145  
ZF TE-ML 06A/06B/06R/06C/07B FORD  
FORD M2C159B/C / M2C86B/C / M2C134D  
CATERPILLAR TO-2 ALLISON C-4  
SPERRY VISKERS/EATON M2950S/I-280-S  
SAUER SUNSTRAND/DANFOSS  
HYDROSTATIC TRANS FLUID/SUITABLE FOR WET BRAKES

Product Characteristics:

Test	Method	Unit	Result
SAE-class			10W-30
Density at 15 °C	D 1298	kg/m <sup>3</sup>	870
Viscosity at 40 °C	D 445	CSt	67,97
Viscosity at 100 °C	D 445	CSt	10,83
Viscosity at -25 °C	D 5293	CP	4827
Viscosity index	D 2270		150
Flash point COC	D 92	°C	226
Pour point	D 97	°C	-35
TBN	D 2896	gKOH/kg	10,28

Volume:

10L	MN2501-10	208L	MN2501-DR
20L	MN2501-20	1000L	MN2501-IBC
60L	MN2501-60		



[www.mannol.de](http://www.mannol.de)

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

# MANNOL®