

Product Code:

7512

SPECIAL PLUS

HC Synthese engine oil

Meets the requirements:

SAE 10W-30, API SN, ACEA A3/B3,
MB 229.1, VW-Norm 501 01/505 00

MANNOL Special Plus is a synthetic blend engine oil, developed for use in petrol and diesel engines. Highly resistant to ageing. It effectively reduces the formation of scale.

Product Characteristics:

Test	Method	Unit	Result
Density at 15°C	D 1298	kg/m ³	870
Viscosity at 40°C	D 445	CSt	66,33
Viscosity at 100°C	D 445	CSt	10,43
Viscosity at -25°C	D 5293	CP	4792
Viscosity index	D 2270		145
Flash point COC	D 92	°C	224
Pour point	D 97	°C	-40
TBN	D 2896	gKOG/kg	9,38

Volume:

1L	MN7512-1	20L	MN7512-20
4L	MN7512-4	60L	MN7512-60
5L	MN7512-5	208L	MN7512-DR
7L	MN7512-7	1000L	MN7512-IBC
10L	MN7512-10		



www.mannol.de

SCT-Vertriebs GmbH
Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®